



| Ratio | Rated Input | | Rated Input Power | | Rated Output torque da Nm | Weight Kg | Type | Lubricant | |
|-------|-------------|----|-------------------|---------------------------------|---------------------------|-----------|--------------------------|-------------|--|
| | rpm | CV | KW | Grease <input type="checkbox"/> | | | | Quantity Kg | |
| 1:1 | 540 | 55 | 40.3 | 69.3 | 22 | SAE 90EP | <input type="checkbox"/> | 12 | |

| Bevel Couplings | | | | | | Cylindrical Couplings | | | | | | Bearings | | | |
|-----------------|----------|--------------|----|----|----|-----------------------|---------|----------|--------------|----|----|----------|--------|---|---|
| Helical | Straight | Teeth Number | | | | Module | Helical | Straight | Teeth Number | | | | Module | A | B |
| | | Z1 | Z2 | Z3 | Z4 | | | | n | Z1 | Z2 | Z3 | | | |
| | X | 18 | 18 | | | 6.15 | | | | | | | | C | D |

| Components Material | | | | |
|---------------------|-----------|-----------|------------|-----------|
| Casing | Shaft X | Shaft Z | Bevel Gear | Spur Gear |
| ASTM 60-40-18 | AISI 3115 | AISI 3120 | AISI 3120 | |

BEVEL GEAR